



WASTE OIL TANK RANGE

Sales: + 44 (0) 1889 567700
Fax: +44 (0) 1889 567600
Email: sales@tuffa.co.uk
Web: www.tuffa.co.uk

TECHNICAL INFORMATION

Length: 2680mm
Width: 870mm
Height: 1665mm
Capacity: 1350 litres
Approx Weight: 200 kilograms
Material: Medium density polyethylene
UV Stabilised: Yes

NOTE: Dimensions are approximate—due to shrinkage.

PRODUCT DESCRIPTION

1350 bunded waste oil tank

SPECIFICATION

- ◇ Vent
- ◇ Tun dish – sited at a suitable height for pouring waste oil into
- ◇ Gas strut assisted flip lid for ease when opening the lid of the tank

OPTIONAL EXTRAS

- ◇ Fire protection - Tuffa UK has pioneered the fire protected oil tank, and developed a patented high quality fire retardant material mounted between the primary tank and outer layer of the tank. This approach has been tested and certified to BS476 to give at least 30 and 60 minutes protection by Warrington Fire Research Centre (now Bodycote Global) and is suitable for both domestic and commercial applications.
- ◇ Suction points available at various sizes
- ◇ Contents Gauge
- ◇ Pumping System
- ◇ Larger sizes available



Capacity (litres)	1350
Length (mm)	2680
Width (mm)	870
Height (mm)	1665

1350 SLBWOS Waste Oil Tank





BUNDED TANK RANGE

Sales: + 44 (0) 1889 567700

Fax: +44 (0) 1889 567600

Email: sales@tuffa.co.uk

Web: www.tuffa.co.uk

Key Benefits

The bund contains a minimum 110% volume of the inner tank

The banded construction offers integral protection from leakage and overfilling

The covered bund prevents the collection of rainwater and debris

Lockable outer cabinet (larger models), flip lid (smaller models) allowing access to all equipment

An overflow prevention device is fitted to all larger banded tanks; automatic shut off when the tank is full

Made from recyclable polyethylene

Corrosion resistant

UV stabilised

