



Specification

Tuffa 2500HBFP/60

TECHNICAL INFORMATION

Length:	2820mm
Width:	1500mm
Height:	1650mm
Approx Capacity:	2500 litres
	<i>This is reduced by the overfill prevention valve *</i>
Approx Weight:	320 kilograms
Material:	Medium density polyethylene
UV Stabilised:	Yes
Fill:	2" BSP
Fire Retardant:	60 minute

PRODUCT DESCRIPTION

2500 litres bunded, fire protected tank.

SPECIFICATION

- ◇ 2" BSP fill connection c/w cap and chain
- ◇ Vent
- ◇ Gas strut assisted flip lid for ease when opening the lid of the tank
- ◇ 1" bottom outlet (10mm top outlet available upon request)
- ◇ Overfill prevention valve *this reduces the working capacity
- ◇ Clock gauge
- ◇ 60 minute fire retardant material
- ◇ Electronic Watchman contents gauge

OPTIONAL EXTRAS

- ◇ Fire protection - Tuffa UK has pioneered the fire protected oil tank, and developed a patented high quality fire retardant material mounted between the primary tank and outer layer of the tank. This approach has been tested and certified to BS476 to give at least 30 and 60 minutes protection by Warrington Fire Research Centre (now Bodycote Global) and is suitable for both domestic and commercial applications.
- ◇ Fittings Pack (1" - 1/2" adaptor, ball valve and filter)

Issued 01.02.10



Your in-house Liquid Storage Solution Partners

Manufacturers of plastic and steel liquid storage tanks up to 100,000 litres.

Easi-fill Bunded Range

Easi-fill Fuel Stations

Interlinked Tanks

Dual & Triple storage compartment tanks

Biodiesel Storage

Tank Fire Protection

Waste Oil tanks, Bowsers & Chemical Tanks

Petrol Storage

Rain Water Harvesting

AdBlue Systems

T: 01889 567700
F: 01889 567600



www.tuffa.co.uk
sales@tuffa.co.uk



Registered office address:

TUFFA UK Limited
Dovefields Industrial Estate
Derby Road
Uttoxeter
Staffordshire



VAT Reg No.: 861 420 544
Company Reg: 5444911

