



Specification

Tuffa 3500VB

TECHNICAL INFORMATION

Diameter:	2000mm
Height:	2500mm
Capacity:	3500 litres
Approx Weight:	350 kilograms
Material:	Medium density polyethylene
UV Stabilised:	Yes
Fill:	2" BSP

PRODUCT DESCRIPTION

3500 litres bunded tank.

SPECIFICATION

- ◆ 2" BSP fill connection c/w cap and chain (located on top of tank)
- ◆ Vent
- ◆ Contents Gauge
- ◆ 1" bottom outlet (top outlet available upon request)
- ◆ Overfill prevention valve

OPTIONAL EXTRAS

- ◆ Fire Protection—The Tuffa FireStop is our patented Fire Protection for oil storage tanks and can be fitted to all of our Bunded range of tanks. It can be supplied in 30 / 60 minutes fire/thermal protection and 120 minute fire protection where required. It meets the methodology in BS5410: Part 1: Section 6.3 and the material is independently tested to BS476.
- ◆ Cabinet—includes H&S low level fill point, battery bund / overfill alarm
- ◆ Higher accuracy contents gauge

Manufacturers of plastic and steel liquid storage tanks up to 100,000 litres.

Easi-fill Bunded Range

Easi-fill Fuel Stations

Interlinked Tanks

Dual & Triple storage compartment tanks

Biodiesel Storage

Tank Fire Protection

Waste Oil tanks, Bowsers & Chemical Tanks

Petrol Storage

Rain Water Harvesting

AdBlue Systems

Issued 01.02.10



Your in-house Liquid Storage Solution Partners

T: 01889 567700
F: 01889 567600



www.tuffa.co.uk
sales@tuffa.co.uk



Registered office address:

TUFFA UK Limited
Dovefields Industrial Estate
Derby Road
Uttoxeter
Staffordshire



VAT Reg No.: 861 420 544
Company Reg: 5444911

