



240volt ATEX pump

Technical Information

Length:	2800mm
Width:	1400mm
Height:	700mm
Capacity:	1950 litres
Filler neck:	4" BSP
Fuel delivery:	Hand pump c/w hose and 3/4" nozzle

Product Description

1950 litres static bunded petrol tank. Ideal for storing petrol safely, legally and securely on site. It is high security, integrally bunded, has a painted steel construction and comes fully fire protected. There is a overall tank height of 0.8m to receive gravity feed deliveries by tanker. The unit should be sited in the open air two to four metres away from any buildings on a concrete base. The petrol tank is designed and manufactured to meet the Requirements of: HSG176 (The Storage of Flammable Liquids in Tanks) and HSG51 (The Storage of Flammable Liquids in Containers).

Specification

- ◆ High Quality Hand Pump
- ◆ Flowmeter with Totalizer
- ◆ 4" tanker inlet connection c/w cap and chain
- ◆ Heavy duty tank lid with hydraulic lift rams fully lockable
- ◆ Bund Vent Cap
- ◆ Quality delivery hose
- ◆ Small nozzle to fit the smallest of machines
- ◆ Fork Lift Skids
- ◆ 3.7m Breather pipe with Flame Arrestor Vent Cap
- ◆ Calibrated Dip Stick
- ◆ Earth Strap and Rod
- ◆ Tank Bolt Down points
- ◆ Full Fire Protection

Optional Extras

- ◆ 240v ATEX pump c/w flowmeter, 3m x 3/4" delivery hose & automatic shut of nozzle
- ◆ Hose Reel (various lengths available)

