FirePro® Oil Tanks

FirePro® is a bunded oil tank with an integrally fitted, patented fire jacket providing **30- or 60-minute** fire protection, allowing installation **as close as 300mm** from building and boundaries.

FirePro® Oil Tanks / Plastic

1350SLBFP

Capacity	Length	Width	Height	Weight 30min	Weight 60min
1,150 litres	2,680mm	870mm	1,665mm	195kg	238kg

1400VBFP

Capacity	Diameter	Height	Weight 30min	Weight 60min
1,200 litres	1,585mm	1,750mm	140kg	171kg

2500HBFP

Capacity	Length	Width	Height	Weight 30min	Weight 60min
2,440 litres	2,840mm	1,520mm	1,630mm	290kg	337kg

FirePro® Oil Tanks / Steel

1000SBFP

Capacity	Length	Width	Height	Weight 30min	Weight 60min
1,000 litres	1,800mm	600mm	1,680mm	340kg	370kg

1650SBFP

Capacity	Length	Width	Height	Weight 30min	Weight 60min
1,650 litres	1,800mm	900mm	1,680mm	410kg	455kg

2300SBFP

Capacity	Length	Width	Height	Weight 30min	Weight 60min
2,300 litres	1,800mm	1,200mm	1,680mm	478kg	510kg

Who can sign-off and certify a FirePro® tank?

A Tuffa FirePro® installation requires an independent sign-off to comply with building regulations. Failure to do so would render an installation incompliant.

There are three options:

1. Stroma approved persons inspection. Do not install prior to sign-off. Applications need to be submitted at least 7 working days before installation.
2. Self-certification through a competent person scheme (APHC).
3. Certification via a building notice by local authority building control.

Find out more about the ease of signing off a Tuffa fire-rated oil tank by visiting www.tuffa.co.uk/buyers-guides/guide-to-firepro-sign-off

Scan now to find out more

STROMA BUILDING CONTROL

SUPPLIER MEMBER APHC ASSOCIATION OF PLUMBING & HEATING CONTRACTORS LIMITED

Oil Tanks

Bunded Oil Tanks / Plastic

1250SLB

NEW FOR 2026

Capacity	Length	Width	Height	Weight
1,250 litres	2,100mm	600mm	1,805mm	180kg

Market-Leading 600mm Ultra-Slim Profile: The narrowest tank of its capacity on the market, purposely engineered to navigate tight side alleys and standard garden gates.

1350SLB

Capacity	Length	Width	Height	Weight
1,350 litres	2,680mm	870mm	1,665mm	170kg

1400VB

Capacity	Diameter	Height	Weight
1,400 litres	1,585mm	1,750mm	120kg

2500HB

Capacity	Length	Width	Height	Weight
2,500 litres	2,840mm	1,520mm	1,630mm	260kg

3500VB

Capacity	Diameter	Height	Weight
3,500 litres	2,013mm	2,520mm	280kg

6000VB

Capacity	Diameter	Height	Weight
6,000 litres	2,550mm	2,585mm	360kg

10000VB

Capacity	Diameter	Height	Weight
10,000 litres	2,890mm	2,590mm	430kg

15000VB

Capacity	Diameter	Height	Weight
15,000 litres	2,890mm	3,500mm	630kg

30000VB*

Length	Width	Height
6,020mm	3,460mm	3,500mm

Capacity	Weight**
30,000 litres	1,260kg

* x2 15000VB interlinked
** approximate

Bunded Oil Tanks / Steel

1000SB

Capacity	Length	Width	Height	Weight
1,000 litres	1,800mm	600mm	1,680mm	320kg

1650SB

Capacity	Length	Width	Height	Weight
1,670 litres	1,800mm	900mm	1,680mm	380kg

2300SB

Capacity	Length	Width	Height	Weight
2,325 litres	1,800mm	1,200mm	1,680mm	450kg

Scan to find out more

sales@tuffa.co.uk / 01889 567700 / www.tuffa.co.uk