



## BUNDED FUEL STATION RANGE

Sales: + 44 (0) 1889 567700  
Fax: +44 (0) 1889 567600  
Email: sales@tuffa.co.uk  
Web: www.tuffa.co.uk

### TECHNICAL INFORMATION

Diameter: 2890mm  
Height: 2600mm  
Capacity: 10000 litres  
Approx Weight: 490 kilograms  
Material: Medium density polyethylene  
UV Stabilised: Yes  
Fill: 2" BSP

NOTE: Dimensions are approximate — due to shrinkage.

### PRODUCT DESCRIPTION

10000 banded diesel tank. Ideal for re-fuelling vehicles and machinery.

### SPECIFICATION

- ◇ 2" BSP fill connection c/w cap and chain
- ◇ Vent
- ◇ Lockable fill point cabinet to house all appropriate equipment
- ◇ FMS combining of High Accuracy Contents Level Gauge and Bund & Overfill Alarm (240V)
- ◇ A submersible pump, approximately 60lpm. \* 240 volt
- ◇ A digital flowmeter
- ◇ 4 metres of delivery hose and automatic shut off nozzle
- ◇ 10 micron filtration
- ◇ Key switch – to operate the pump
- ◇ Nozzle holster
- ◇ Overfill prevention valve
- ◇ Colour: Black

### OPTIONAL EXTRAS

- ◇ Fire Protection—The Tuffa FireStop is our patented Fire Protection for oil storage tanks and can be fitted to all of our Banded range of tanks. It can be supplied in 30 / 60 minutes fire/thermal protection and 120 minute fire protection where required.
- ◇ Extra length delivery hose
- ◇ A light within the cabinet
- ◇ Hose reel – various lengths
- ◇ Higher output pump
- ◇ Armco protection barrier
- ◇ High security steel cabinet with roller shutter door
- ◇ Fuel management systems
- ◇ Water and particulate filtrations
- ◇ Various colours available



Capacity (litres)	10000
Diameter (mm)	2890
Height (mm)	2600

**10000 VBFS** Bunded Fuel Station





## BUNDED TANK RANGE

Sales: + 44 (0) 1889 567700

Fax: +44 (0) 1889 567600

Email: sales@tuffa.co.uk

Web: www.tuffa.co.uk

### Key Benefits

Suitable for agricultural, commercial and industrial applications

Refuelling equipment easily accessible from ground level

The bund contains a minimum 110% volume of the inner tank

The banded construction offers integral protection from leakage and overfilling

The covered bund prevents the collection of rainwater and debris

Lockable outer cabinet (larger models), flip lid (smaller models) allowing access to all equipment

An overfill prevention device is fitted to all larger banded tanks; automatic shut off when the tank is full

Made from recyclable polyethylene

Corrosion resistant

UV stabilised

