



## BUNDED TANK RANGE

Sales: + 44 (0) 1889 567700  
Fax: +44 (0) 1889 567600  
Email: sales@tuffa.co.uk  
Web: www.tuffa.co.uk

### TECHNICAL INFORMATION

Length: 2680mm  
Width: 870mm  
Height: 1665mm  
Capacity: 1300 litres  
Approx Weight: 200 kilograms  
Material: Medium density polyethylene  
UV Stabilised: Yes  
Fill: 2" BSP

NOTE: Dimensions are approximate—due to shrinkage.

### PRODUCT DESCRIPTION

1350 litre banded tank.

### SPECIFICATION

- ◇ 2" BSP fill connection c/w cap and chain
- ◇ Vent
- ◇ Clock gauge
- ◇ Gas strut assisted flip lid
- ◇ 1" bottom outlet (top outlet available upon request)
- ◇ Colour: Black with clear inner tank
- ◇ Fittings Kit (1" - 1/2" adaptor, ball valve and filter)



Capacity (litres)	1350
Length (mm)	2680
Width (mm)	870
Height (mm)	1665

### 1350 SLB Banded Fuel Tank



### OPTIONAL EXTRAS

- ◇ Fire Protection—The Tuffa FireStop is our patented Fire Protection for oil storage tanks and can be fitted to all of our Banded range of tanks. It can be supplied in 30 / 60 minutes fire/thermal protection and 120 minute fire protection where required.
- ◇ Electronic watchman contents gauge.
- ◇ Various colours available





## BUNDED TANK RANGE

Sales: + 44 (0) 1889 567700  
Fax: +44 (0) 1889 567600  
Email: sales@tuffa.co.uk  
Web: www.tuffa.co.uk

### Key Benefits

The bund contains a minimum 110% volume of the inner tank

The banded construction offers integral protection from leakage and overfilling

The covered bund prevents the collection of rainwater and debris

Lockable outer cabinet (larger models), flip lid (smaller models) allowing access to all equipment

An overfill prevention device is fitted to all larger banded tanks; automatic shut off when the tank is full

Made from recyclable polyethylene

Corrosion resistant

UV stabilised

