



FIRE PROTECTED TANK RANGE

Sales: + 44 (0) 1889 567700
 Fax: +44 (0) 1889 567600
 Email: sales@tuffa.co.uk
 Web: www.tuffa.co.uk

TECHNICAL INFORMATION

Length: 2680mm
 Width: 870mm
 Height: 1665mm
 Approx Working Capacity: 1150 litres
 Approx Weight: 230 kilograms
 Material: Medium density polyethylene
 UV Stabilised: Yes
 Fill: 2" BSP
Fire Retardant: 30 minute or 60 minute

NOTE: Dimensions are approximate—due to shrinkage.

PRODUCT DESCRIPTION

1350 banded, fire protected tank.

SPECIFICATION

- ◊ Integral Fire retardant material
- ◊ 2" BSP fill connection c/w cap and chain
- ◊ Vent
- ◊ Gas strut assisted flip lid
- ◊ 1" bottom outlet (10mm top outlet available upon request)
- ◊ Overfill prevention valve *this reduces the working capacity
- ◊ Clock gauge
- ◊ Electronic Watchman contents gauge
- ◊ Colour: Black (other colours including Green available on request)
- ◊ Fittings Pack (1" - 1/2" adaptor, ball valve and filter)

OPTIONAL EXTRAS

- ◊ Lockable Fill Cap



Capacity (litres)	1150 *
Length (mm)	2680
Width (mm)	870
Height (mm)	1665

1350 SLBFP 30 min / 60 min





FIRE PROTECTED TANK RANGE

Sales: + 44 (0) 1889 567700
Fax: +44 (0) 1889 567600
Email: sales@tuffa.co.uk
Web: www.tuffa.co.uk

Key Benefits

The bund contains a minimum 110% volume of the inner tank

The banded construction offers integral protection from leakage and overfilling

The covered bund prevents the collection of rainwater and debris

Lockable outer cabinet (larger models), flip lid (smaller models) allowing access to all equipment

An overfill prevention device is fitted to all larger banded tanks; automatic shut off when the tank is full

Made from recyclable polyethylene

Corrosion resistant

UV stabilised

Steel Fire Protected Tanks also available

