



BUNDED FUEL STATION RANGE

Sales: + 44 (0) 1889 567700
Fax: +44 (0) 1889 567600
Email: sales@tuffa.co.uk
Web: www.tuffa.co.uk

TECHNICAL INFORMATION

Length: 2680mm
Width: 870mm
Height: 1665mm
Capacity: 1350 litres
Approx Weight: 220 kilograms
Material: Medium density polyethylene
UV Stabilised: Yes
Fill: 2" BSP

NOTE: Dimensions are approximate — due to shrinkage.

PRODUCT DESCRIPTION

1350 banded diesel tank. Ideal for re-fuelling vehicles and machinery.

SPECIFICATION

- ◊ 2" BSP fill connection c/w cap and chain
- ◊ Vent
- ◊ Clock gauge
- ◊ Gas strut assisted flip lid for ease when opening the lid of the tank
- ◊ A submersible pump * 240 volt
- ◊ A digital flowmeter
- ◊ 4 metres of delivery hose and automatic shut off nozzle
- ◊ 10 micron filtration
- ◊ Nozzle holster
- ◊ Colour: Black

OPTIONAL EXTRAS

- ◊ Fire Protection—The Tuffa FireStop is our patented Fire Protection for oil storage tanks and can be fitted to all of our Banded range of tanks. It can be supplied in 30 / 60 minutes fire/thermal protection and 120 minute fire protection where required.
- ◊ 12 volt / 24 volt external pump
- ◊ Extra length delivery hose
- ◊ Key switch – to enable and disable the pump
- ◊ Electronic watchman contents gauge
- ◊ Water and particulate filtration
- ◊ Replacement filter elements
- ◊ Fuel Management Systems
- ◊ Various colours available





BUNDED TANK RANGE

Sales: + 44 (0) 1889 567700

Fax: +44 (0) 1889 567600

Email: sales@tuffa.co.uk

Web: www.tuffa.co.uk

Key Benefits

Suitable for agricultural, commercial and industrial applications

Refuelling equipment easily accessible from ground level

The bund contains a minimum 110% volume of the inner tank

The banded construction offers integral protection from leakage and overfilling

The covered bund prevents the collection of rainwater and debris

Lockable outer cabinet (larger models), flip lid (smaller models) allowing access to all equipment

An overfill prevention device is fitted to all larger banded tanks; automatic shut off when the tank is full

Made from recyclable polyethylene

Corrosion resistant

UV stabilised

