

TECHNICAL SPECIFICATION



| | |
|----------------------|--|
| MODEL: | TUFFA 1350SLBFP Fire Protected Tank |
| CAPACITY (l): | 1150 |
| LENGTH (mm): | 2680 |
| WIDTH (mm): | 870 |
| HEIGHT (mm): | 1665 |
| WEIGHT (kg): | 30min - 225 60min - 268 |
| MATERIAL: | Lower Linear Density Polyethylene |
| BUNDED: | |

NEED MORE INFORMATION?

CALL US ON:
01889 567700



SPECIFICATION

- ▶ Bunded construction
- ▶ Fire protection
- ▶ 2" BSP fill connection with cap & chain
- ▶ Vent
- ▶ Manual float level gauge
- ▶ Electronic remote reading gauge
- ▶ 1" bottom outlet (top outlet available on request)
- ▶ Overfill prevention valve
- ▶ Tank pack (1" - 1/2" adaptor, ball valve & filter)
- ▶ Lockable flip lid

ACHIEVEMENTS

- ▶ Independently tested to BS476: Part 22: 1987
- ▶ Independently tested to BS476 (Warrington Fire Research Centre)
- ▶ Meets Section J 5.4 of Building Regulations, Table 5.1 for Fire Protection for Oil Storage Tanks
- ▶ LABC System Approval (Local Authority Building Control)

30 and 60 minute fire protection available



Tuffa UK Limited
Dovefields Industrial Estate,
Derby Road, Uttoxeter
Staffs, ST14 8SW



... for all your liquid storage needs

Contact us on T: 01889 567700 | E: sales@tuffa.co.uk | W: www.tuffa.co.uk